







Contactors Assemblies

3RA13, 3RA14 Contactor Assemblies

SIRIUS 3RA13 reversing contactor assemblies









For contactors	Size	Version	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*	PG
Assembly kits for making 3-pole contactor assemblies								
 3RT101 3RA1913-2A	S00	The assembly kit contains: mechanical interlock, 2 connecting clips for 2 contactors wiring modules on the top and bottom	▶	3RA1913-2A		1	1 unit	41B
 3RT102 3RA1923-2A	S0	The assembly kit contains: wiring modules on the top and bottom	▶	3RA1923-2A		1	1 unit	41B
 3RT103 3RA1933-2A	S2	The assembly kit contains: 2 connecting clips for 2 contactors wiring modules on the top and bottom	▶	3RA1933-2A		1	1 unit	41B
 3RT104 3RA1943-2A	S3	The assembly kit contains: 2 connecting clips for 2 contactors wiring modules on the top and bottom	▶	3RA1943-2A		1	1 unit	41B
 3RT105 3RA1953-2A	S6	The assembly kit contains: wiring modules on the top and bottom (for connection with box terminal)	A	3RA1953-2A		1	1 unit	41B
 3RT1.6 3RA1953-2M	S6	The assembly kit contains: wiring modules on the top and bottom (for connection without box terminal)	A	3RA1953-2M		1	1 unit	41B
	S10		A	3RA1963-2A		1	1 unit	41B
	S12		A	3RA1973-2A		1	1 unit	41B

Load Feeders and Motor Starters for Use in the Control Cabinet

SIRIUS 3RA1 Load Feeders

Accessories

Accessories for 3RA1 direct-on-line and reversing starters

	For motor starter protectors Size	For contactors Size	Version	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*	PG
Link modules									
	Electrical and mechanical link between motor starter protector and contactor.								
	Single-unit packaging								
3RA1911-1A			<u>Actuating voltage of contactor</u>						
	S00	S00	AC and DC	▶	3RA1911-1AA00		1	1 unit	41B
	S0	S00		▶	3RA1921-1DA00		1	1 unit	41B
	S0	S0	AC	▶	3RA1921-1AA00		1	1 unit	41B
	S2	S2		▶	3RA1931-1AA00		1	1 unit	41B
	S3	S3		▶	3RA1941-1AA00		1	1 unit	41B
	S0	S0	DC	▶	3RA1921-1BA00		1	1 unit	41B
	S2	S2		▶	3RA1931-1BA00		1	1 unit	41B
	S3	S3		▶	3RA1941-1BA00		1	1 unit	41B
									
	Multi-unit packaging								
			<u>Actuating voltage of contactor</u>						
	S00	S00	AC and DC	▶	3RA1911-1A		1	10 units	41B
	S0	S00		▶	3RA1921-1D		1	10 units	41B
	S0	S0	AC	▶	3RA1921-1A		1	10 units	41B
	S2	S2		▶	3RA1931-1A		1	5 units	41B
	S3	S3		▶	3RA1941-1A		1	5 units	41B
	S0	S0	DC	▶	3RA1921-1B		1	10 units	41B
	S2	S2		▶	3RA1931-1B		1	5 units	41B
	S3	S3		▶	3RA1941-1B		1	5 units	41B
3RA1931-1A									
Hybrid link modules									
	Screw terminals	Cage Clamp terminals	Electrical and mechanical connection between motor starter protector with screw terminals and contactor with Cage Clamp terminals						
									
	Single-unit packaging								
			<u>Actuating voltage of contactor</u>						
	S00	S00	AC and DC	▶	3RA1911-2FA00		1	1 unit	41B
	S0	S00		▶	3RA1921-2FA00		1	1 unit	41B
									
	Multi-unit packaging								
			<u>Actuating voltage of contactor</u>						
	S00	S00	AC and DC	▶	3RA1911-2F		1	10 units	41B
	S0	S00		▶	3RA1921-2F		1	10 units	41B
3RA1921-2FA00									
Wiring kit									
	--	S00	Reversing duty Electrical and mechanical link for reversing contactors.	▶	3RA1913-2A		1	1 unit	41B
		S0	Can be combined with link module.	▶	3RA1923-2A		1	1 unit	41B
	S2			▶	3RA1933-2A		1	1 unit	41B
	S3			▶	3RA1943-2A		1	1 unit	41B
3RA1913-2A			For size S00: Optionally with integrated electrical and mechanical locking device. For sizes S0 to S3: Mechanical locking device must be ordered separately.						
	--	S00	Star-delta (wye-delta) starting Electrical and mechanical link for three contactors of same size	A	3RA1913-2B		1	1 unit	41B
		S0		▶	3RA1923-2B		1	1 unit	41B
		S2		▶	3RA1933-2B		1	1 unit	41B
		S3		▶	3RA1943-2B		1	1 unit	41B
Connection modules for contactors with screw terminals (can only be used for direct-on-line starters)									
	Size S00, S0		Adapters for contactors Ambient temperature $T_{u \text{ max.}} = 60 \text{ °C}$						
	--	S00	Size S00, rated operational current I_e at AC-3/400 V: 20 A	B	3RT1916-4RD01		1	1 unit	41B
3RT1926-4RD01	--	S0	Size S0, rated operational current I_e at AC-3/400 V: 25 A	B	3RT1926-4RD01		1	1 unit	41B
	--	S00, S0	Plugs for contactors Size S00, S0	B	3RT1900-4RE01		1	1 unit	41B
	3RT1900-4RE01								