

IN-LINE - 900, 1500 CFM

Single, impact resistant centrifugal blower wheel driven by low RPM motor. Housing dimensions: 22" x 18" x 18" (55.9 cm x 45.7 cm x 45.7 cm). Two 8" x 12" (20.3 cm x 30.5 cm) duct connectors. In-line models have removable access panel and do not include insulation. AMCA certified.



Part No.	Description	CFM (Horiz. / Vert.) @ 0.1"SP	Sones (Horiz. / Vert.) @ 0.1"SP	Duct	Weight (lb.)	UPC
L900L	In-line, 120 VAC	902 / 778	3.8 / 4.5	8" x 12"	64.4	026715124671
L1500L	In-line, 120 VAC	1228 / 1117	6.8 / 7.8	8" x 12"	64.5	026715124688

CABINET VENTILATOR - 2000 CFM

Twin double inlet blower wheels with housing measuring 14 5/8" x 14 5/8" x 38". AMCA certified.



Part No.	Description	CFM (Horiz. / Vert.) @ 0.1"SP	Sones (Horiz. / Vert.) @ 0.1"SP	Duct	Weight (lb.)	UPC
L2000L	In-line, 120 VAC	1803 / 1931	9.8 / 10.3	7 3/4" x 33 3/4"	89.0	026715124695

ACCESSORIES



Part No.	Description	Weight (lb.)	Std. Pack	UPC
MG1	Metal grille kit for LoSone® housing no.1	1.9	1 pc.	026715131969
80L	Speed Control for LoSone® fans, 120 V, 3 amps	0.4	1 pc.	026715172269
RD1	Radiation damper: 12 1/2" x 12 1/2" for use with L100, L150, L200, L250 and L300 models.	3.7	1 pc.	026715124749

IN-LINE ADAPTERS



Part No.	Description	Weight (lb.)	Std. Pack	UPC
961L	Use with L100 and L150 series, for 6" (15.2 cm) round duct intake	1.65	1 pc.	026715131884
981L	Use with L200, L250, L300 series; for 8" (20.3 cm) round duct intake	1.85	1 pc.	026715124718
982L	Use with L400, L500, L700 series; for 4 1/2" x 18 1/2" (11.4 cm x 47 cm) duct intake	3.0	1 pc.	026715124725