

596-00665



Article Number: 596-00665

Solar Label, Warning- Dual Power Source Label, 4.12" X .75", Vinyl, Orange/White,10/pkg



Download drawing



Download spec sheet

## Base Data

Local Order Number 596-00665

Type WDPSLBL10

Color Red (RD)

- Features and Benefits**
- Made with UV stable inks and materials for durability and weather resistance
  - Supplied with aggressive adhesive to ensure long life
  - Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections
  - Pre-printed labels offer significant time and cost savings over high priced engraved and lead time purchased markers

**Product Description** HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2011) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

**Technical Description** 4.12" X .75" Black text on an Orange background that reads as," WARNING - DUAL POWER SOURCE SECOND SOURCE IS PV SYSTEM." 10 per pkg.

**Short Description** Solar Label, Warning- Dual Power Source Label, 4.12" X .75", Vinyl, Orange/White,10/pkg

## Product Dimensions

Width W (Imperial) 4.12 "

Width W (Metric) 104.6 mm

Height H (Imperial) 0.75 "

Height H (Metric) 19.05 mm

## Logistics and Packaging

Quantity Per pack

Package Quantity 10

Package Quantity (Metric) 10

## Material and Specifications

Material Vinyl

Material Shortcut VL

Adhesive Acrylic

Adhesive Shortcut Acrylic

Adhesive Operating Temperature -40°F to +174°F (-40°C to +79°C)

Halogenfree Yes

**Operating Temperature** -40°F to +174°F (-40°C to +79°C)

**ROHS Compliant** Yes

**UL Recognized (US)** Yes