

MULTIPLE CONNECTORS Used In Neutral Assemblies And Grounding Applications




FEATURES

- Multiple connectors are made from either copper or aluminum bar and can be used in a variety of neutral and grounding applications.
- Aluminum connectors are fin plated for low contact resistance and are suitable for use with copper or aluminum conductors. Aluminum connectors are dual rated for use with aluminum and copper cables.
- Copper connectors are suitable for use with copper wire only. The
- 4-14 AWG multiple connectors can be custom made in any number of wire holes up to 190 holes.
- Contact NSi for price and delivery information.

RATINGS



CAT. NO.	MATERIAL
4-14 (32)	Aluminum
4-14 (53)	Aluminum
4-14 (63)	Aluminum
4-14 (74)	Aluminum
4-14 (614)	Aluminum
4-14 (717)	Aluminum
4-14 (726)	Aluminum
4-14 (847)	Aluminum
4-14 (937)	Aluminum
4-14 (11111)	Aluminum
4-14 (12112)	Aluminum
4-14 (14114)	Aluminum
4-14 (17117)	Aluminum
4-14 (22122)	Aluminum
4-14 (190)*	Aluminum
2-14 (12311)**	Aluminum
2/0-14 (32)**	Aluminum
2/0-14 (524)**	Aluminum
2/0-14 (818)**	Aluminum
4C-14 (616)	Copper
4C-14 (717)	Copper
4C-14 (818)	Copper
4C-14 (14114)	Copper
4C-14 (15313)	Copper
4C-14 (15611)	Copper
4C-190*	Copper
2C-14 (515)	Copper
2C-14 (827)	Copper



WIRE RANGE	NO. OF CIRCUITS	TOTAL NO. OF HOLES	LENGTH	HEIGHT	WIDTH	HOLE SPACING	MTNG. HOLE POSITION	STD. CTN. QTY.
4-14	2	3	0.950	0.440	0.310	0.312	2	100
4-14	4	5	1.570	0.440	0.310	0.312	3	100
4-14	5	6	1.880	0.440	0.310	0.312	3	100
4-14	6	7	2.250	0.440	0.310	0.312	4	100
4-14	4	6	1.880	0.440	0.310	0.312	1 & 4	100
4-14	5	7	2.250	0.440	0.310	0.312	1 & 7	100
4-14	5	7	2.250	0.440	0.310	0.312	2 & 6	100
4-14	6	8	2.560	0.440	0.310	0.312	4 & 7	100
4-14	7	9	2.870	0.440	0.310	0.312	3 & 7	100
4-14	9	11	3.500	0.440	0.310	0.312	1 & 11	50
4-14	10	12	3.810	0.440	0.310	0.312	1 & 12	50
4-14	12	14	4.430	0.440	0.310	0.312	1 & 14	50
4-14	15	17	5.370	0.440	0.310	0.312	1 & 17	50
4-14	20	22	6.930	0.440	0.310	0.312	1 & 22	50
4-14	190	190	60.000	0.440	0.310	0.312	—	10
2-14	10	12	4.120	0.500	0.380	0.340	3 & 11	50
2/0-14	2	3	1.750	0.750	0.560	0.601	2	25
2/0-14	3	5	2.950	0.750	0.560	0.601	2 & 4	25
2/0-14	6	8	4.750	0.750	0.560	0.601	1 & 8	25
4-14	4	6	1.940	0.440	0.310	0.312	1 & 6	100
4-14	5	7	2.250	0.440	0.310	0.312	1 & 7	100
4-14	6	8	2.56	0.440	0.310	0.312	1 & 8	100
4-14	12	14	4.430	0.440	0.310	0.312	1 & 14	50
4-14	13	15	4.740	0.440	0.310	0.312	3 & 13	50
4-14	13	15	4.740	0.440	0.310	0.312	6 & 11	50
4-14	190	190	60.000	0.440	0.310	0.312	—	10
2-14	3	5	2.000	0.500	0.380	0.397	1 & 5	50
2-14	6	8	3.250	0.500	0.380	0.397	2 & 7	50

*Supplied with screws unassembled.

**Not UL Rated.