

# QO Load Centers – Main Lugs



## Main Lugs

- UL Listed
- Single-Phase, 3-Wire
- 120/240 Vac
- 12 Spaces and Higher Panels Convertible to Main Breaker
- Factory Installed Main Lugs
- Copper Bus Bar Only on 12 Circuits and Higher
- Catalog Number Guide Page 17



QO13040L200GC



QO11624L125GRB

Listings thru 200A mains meet Federal Specification W-P-115c as Type 1, Class 2.

- Not supplied with copper bus bar.

\* Will not accept Qwik-Gard QO GFI circuit breakers.

□ Mains rated 25A when aluminum wire is used.

■ Use #10 maximum size wire for GFI circuit breaker.

\* Contact Square D sales representative for ordering information.

† Item may require additional lead time.

Amps	Spaces	Max. Circuits	Cover	Catalog #	Ground Bar	UPC Code	Box Size
<b>Indoor – 10,000 AIR</b>							(see pg.18)
30	2	2	Surface	QO2L30SCP●*†	PK3GTA1	0-47569-80432-8	1
70	2	4	Flush	QO24L70FCP●■	PK4GTA	0-47569-80435-9	2
	2	4	Surface	QO24L70SCP●■	PK4GTA	0-47569-80436-6	2
100	6	12	Flush	QO612L100FCP●	PK7GTA	0-47569-80508-0	4
	6	12	Surface	QO612L100SCP●	PK7GTA	0-47569-80507-3	4
	6	12	Flush	QO612L100DF●	PK7GTA	7-85901-78564-4	4
	6	12	Surface	QO612L100DS●	PK7GTA	7-85901-78562-0	4
	8	16	Flush	QO816L100FCP●	PK7GTA	0-47569-80475-5	4
	8	16	Surface	QO816L100SCP●	PK7GTA	0-47569-80476-2	4
	8	16	Flush	QO816L100DF●	PK7GTA	7-85901-78569-9	4
	8	16	Surface	QO816L100DS●	PK7GTA	7-85901-78574-3	4
125	4	8	Flush	QO148L125GF*	Included	7-85901-48438-7	21
	4	8	Surface	QO148L125GS*	Included	7-85901-48440-0	21
<b>Indoor – QOM1 Main Frame Size: Convertible to 22,000 AIR Main Breaker</b>							(see pg.18)
125	12	12	Combination	QO112L125GC	Included	7-85901-86845-3	6
	12	24	Combination	QO11224L125GC	Included	7-85901-84120-3	6
	16	16	Order Separately*	QO116L125G	Included	7-85901-84773-1	7
	16	24	Order Separately*	QO11624L125G*	Included	7-85901-84130-2	7
	20	20	Combination	QO120L125GC	Included	7-85901-84786-1	7
	20	24	Order Separately*	QO12024L125G*	Included	7-85901-84777-9	7
	24	24	Order Separately*	QO124L125G*	Included	7-85901-84790-8	7
<b>Indoor – QOM2 Main Frame Size: Convertible to 22,000 AIR Main Breaker</b>							(see pg.18)
150	20	30	Order Separately*	QO12030L150G*	Included	7-85901-84779-3	9
	24	24	Order Separately*	QO124L150G*	Included	7-85901-84791-5	9
	30	30	Order Separately*	QO130L150G*	Included	7-85901-84801-1	9
200	12	12	Order Separately*	QO112L200G*	Included	7-85901-84124-1	9
	30	30	Order Separately*	QO130L200G*	Included	7-85901-84802-8	9
	30	40	Combination	QO13040L200GC	Included	7-85901-84798-4	9
225	42	42	Order Separately*	QO142L225G*	Included	7-85901-86775-3	11
<b>Outdoor – Non-metallic Enclosure</b>							(see pg.19)
60	2	4	Rainproof	QO24L60NRNM	Included	7-85901-32802-5	1NM
<b>Outdoor – 10,000 AIR</b>							(see pg.19)
40	2	2	Rainproof	QO2L40RBCP●■	PK3GTA1	0-47569-80437-3	1R
70	2	4	Rainproof	QO24L70RBCP●■	PK4GTA	0-47569-80438-0	1R
100	6	12	Rainproof	QO612L100RBCP●	PK7GTA	0-47569-80509-7	2R
	8	16	Rainproof	QO816L100RBCP●	PK7GTA	0-47569-80477-9	2R
125	4	8	Rainproof	QO148L125GRB*	Included	7-85901-48439-4	15R
<b>Outdoor – QOM1 Main Frame Size: Convertible to 22,000 AIR Main Breaker</b>							(see pg.19)
125	12	12	Rainproof	QO112L125GRB*	Included	7-85901-86785-2	3R
	12	24	Rainproof	QO11224L125GRB	Included	7-85901-86784-5	3R
	16	24	Rainproof	QO11624L125GRB	Included	7-85901-86788-3	4R
	24	24	Rainproof	QO124L125GRB	Included	7-85901-86799-9	4R
<b>Outdoor – QOM2 Main Frame Size: Convertible to 22,000 AIR Main Breaker</b>							(see pg.19)
150	30	30	Rainproof	QO130L150GRB	Included	7-85901-86808-8	6R
200	12	12	Rainproof	QO112L200GRB	Included	7-85901-86786-9	5R
	30	30	Rainproof	QO130L200GRB	Included	7-85901-86809-5	6R
	30	40	Rainproof	QO13040L200GRB	Included	7-85901-86806-4	6R
225	42	42	Rainproof	QO142L225GRB*	Included	7-85901-86815-6	8R