



Consult the factory to take advantage of our custom capabilities in large quantities.

UV stabilized silicon prevents discoloration

UL listed for damp location (indoor products)

WAC LIGHTING

IP68 rated to be dust tight and submersible up to 5 feet.
UL listed for wet location (outdoor products)

INVISILED® 64

Pro2 InvisiLED®





Actual Size

Power: 4W / ft
Lumens: Up to 330 lm / ft
CRI: 90
Rated Life: 80,000 hours

- Brightest InvisiLED® system available
- Designed for cove or task lighting
- UL listed for damp location
- 5 year warranty

- Maximum run length of 25 feet
- May be field cut every 6 inches at the end of a run
- Smooth and continuous ELV dimming



Tape Selections

System	Color Temp	Length	Qty	Finish
LED-TX24	27 2700K	6IN 6 inches	1	WT White
	30 3000K	1 1 foot	1	
	35 3500K	5 5 feet	1	
	45 4500K	1-40 1 foot	40	

Example: **LED-TX2435-6IN-WT**

"L" Connector

System	Color Temp	Finish
LED-TX24	27 2700K	5L-WT White
	30 3000K	
	35 3500K	
	45 4500K	

Example: **LED-TX2435-5L-WT**

Each "L" connector consumes 2 watt

Class 2 Power Supply for Pro 2 (Required)

Type	Model	Power	Dim	Input	Output
Remote	EN-2460-RB2-T	60W	Yes	120V AC	24V AC
	EN-24100-RB2-T	96W			24V AC
Plug-in	EN-2460-P-AR-T	60W	Yes	120V AC	24V AC
	EN-24100-P-AR-T	96W			24V AC
Remote 277V	EN-24100-277-R	96W	No	277V AC	24V DC

Accessories

Rigid Aluminum Channel	LED-T-CH	5 ft	Includes mounting hardware and diffuser lens Field cuttable
Lead Wire	LED-TC-P-2 LED-TC-P-12	2 ft 12 ft	Alternative lengths for plug-in power supplies
Extension Cable	LED-TC-EXT-144	12 ft	Extends distance between a hard wired power supply or wiring box to a tape section
Low Voltage Wiring Box With Feed	LED-TC-B-2	L: 1½ in W: ¾ in H: 7/8 in	Neatly houses up to two wires with 2" female feed
Low Voltage Wiring Box	LED-T-B	L: 1½ in W: ¾ in H: 7/8 in	Neatly houses up to two wires
Wiring Box With Switch	TB-S	L: 6¼ in W: 1½ in H: 1¼ in	Use when spanning a large gap in a system layout without leaving exposed wiring
Joiner Cable	LED-TC-IC2 LED-TC-IC6 LED-TC-IC12 LED-TC-IC36 LED-TC-IC72	2 in 6 in 12 in 36 in 72 in	Use between tape sections
"L" Connector	LED-TC-L		
3-Way "Y" Connector	LED-TC-Y		
4-Way "X" Connector	LED-TC-X		
End cap	LED-TC-EC	1 cut end cap 1 male end cap	
Mounting Clips	LED-T-CL	10 Qty	
Retrofit Channel	LED-T-RC	36 in	