



Main

Device short name	MX
Product or component type	Voltage release
Device application	Control
Range compatibility	PowerPact B Compact NSXm
Voltage release type	Shunt trip
[Uc] control circuit voltage	24 V AC 24 V DC

Complementary

Control signal type	Impulse Maintained
Impulse duration	>= 20 ms
Threshold tripping voltage	0.7 Un - during opening time
Mounting mode	Clip-on
Response time	< 50 ms
Auxiliary connection terminal	Spring
Wire stripping length	0.31 in (8 mm)

Environment

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1649 - Schneider Electric declaration of conformity	Compliant - since 1649 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.