






Shown actual size: Maestro dimmer and 1-gang Claro wallplate in White (WH).


### Product family features

- True multi-location dimming from every location
- Tap on to preset level; tap off; tap twice for full on; touch rocker to adjust light level
- LEDs indicate light level and glow softly in the dark
- Delayed off provides light as you exit the room
- Line frequency compensation maintains stable light levels despite power line frequency and voltage variations
- Programming allows customized functions
- C•L®, eco-dim and eco-timer models available
- Coordinating Claro®, Satin Colors®, and Stainless Steel wallplates only available separately
- Custom engraving available for wallplates; see p. 237

### Direct load type compatibility




-  Incandescent/halogen lighting
-  Dimmable CFL/LED lighting (screw-base)
-  Magnetic low-voltage lighting
-  Electronic low-voltage lighting
-  Fluorescent lighting
-  LED lighting
-  Switched lighting/fan/motor
-  Ceiling fans
-  Ceiling fan/lights

### Load type requiring load interface

-  Neon/cold cathode lighting

Lighting load interfaces may be applicable for some load type, voltage, and capacity combinations. For additional information, see pp. 255–259.

### Control types

-  Single-pole (one location)
-  3-way (2 locations)
-  Multi-location (up to 10 locations)

**Available finishes**

Use **BOLD** color code in model number (Example: MA-600-**BR**)

Gloss finishes\*



**WH**  
White



**LA**  
Light Almond



**AL**  
Almond



**IV**  
Ivory



**GR**  
Gray



**BR**  
Brown



**BL**  
Black

Satin Colors® finishes\*



**SW**  
Snow



**LS**  
Limestone



**BI**  
Biscuit



**ES**  
Eggshell



**PD**  
Palladium



**TP**  
Taupe



**ST**  
Stone



**BG**  
Bluestone



**PL**  
Plum



**SG**  
Sea Glass



**TQ**  
Turquoise



**GS**  
Goldstone



**DS**  
Desert Stone



**GB**  
Greenbriar



**MS**  
Mocha Stone



**TC**  
Terracotta



**SI**  
Sienna



**HT**  
Hot



**MR**  
Merlot



**MN**  
Midnight



**SS**  
Stainless Steel

Metal finish wallplate\*\*

\* Coordinating wallplates only available separately. For wallplate information, see p. 236.

\*\* Stainless Steel wallplate only available separately and includes black plastic trim/adaptor, visible from side. Match with separate Black (BL) or Midnight (MN) controls. For wallplate information, see p. 236.

## Countdown timer control switches



- Use with exhaust fans to reduce moisture, mold, and mildew in bathrooms
- Use with lighting
- Tap on to start timer (5-60 minutes); tap off; tap twice for full on with no timer action
- Touch rocker to adjust countdown time
- One minute warning before lights/fan go off
- **eco-timer®** model timer ranges from 1-30 minutes and always turns off; no full on option
- Timer advanced programming features available

## Timers

### Countdown timer control switches (5–60 minutes/full on)\*

|                      |                                |
|----------------------|--------------------------------|
| Single-pole          | MA-T51- <b>XX</b> <sup>1</sup> |
| 120V 5A light 3A fan |                                |

|                              |                                  |
|------------------------------|----------------------------------|
| Multi-location/single-pole** | MA-T51MN- <b>XX</b> <sup>1</sup> |
| 120V 5A light 3A fan         |                                  |

Single-pole rated for: incandescent/halogen, magnetic low-voltage, and general purpose fans.

Multi-location rated for: incandescent/halogen, magnetic low-voltage, electronic low-voltage, fluorescents, CFLs, LEDs, and general purpose fans.

For multi-location switching use a companion switch (MA-AS- or MSC-AS-).

### Countdown eco-timer control switch (1–30 minutes)\*

|                      |                                  |
|----------------------|----------------------------------|
| Single-pole          | MA-T530G- <b>XX</b> <sup>2</sup> |
| 120V 5A light 3A fan |                                  |

Rated for: incandescent/halogen, magnetic low-voltage, and general purpose fans.

**XX**<sup>1</sup>: Gloss and Satin Colors® codes, see p.57

**XX**<sup>2</sup>: Available in Gloss White (WH), Ivory (IV), Almond (AL), Light Almond (LA)

Wallplates not included. Order separately, see p.236

All models must be derated if ganged unless otherwise noted, see pp.250–252.

\* Minimum load required, see specification submittal

\*\* **Requires neutral wire connection**