


HALO®



H5ICAT

AIR-TITE™ IC HOUSING



- For insulated ceilings and direct contact with insulation
- AIR-TITE housing prevents airflow between attic and living areas
- Upgraded junction box, bar hanger and plaster frame features

DESCRIPTION

For installations where the housing will be in direct contact with ceiling insulation. Integral thermal protector provides positive protection against over-lamping. Meets restricted air flow requirements and prevents valuable energy dollars from being wasted.

Housing Features

- Housing is thermally protected.
- Socket snaps into trim for consistent lamp positioning.

Plaster Frame Features include:

- Regressed locking screw for securing hanger bars
- Cutouts for easily crimping hanger bars in position
- Halo name embossed on plaster frame Galvanized steel construction. The housing can be removed from plaster frame to provide access to the junction box.

Junction Box Features include:

- UL listed for through branch circuit wiring

- Positioned to accommodate straight conduit runs
- Seven 1/2" trade size conduit knockouts with true pry-out slots
- Slide-N-Side™ connectors allow 14/2 or 12/2 non-metallic sheathed cable to be installed without tools and without removing knockouts.
- Three quick connect wire connectors eliminate need for additional wire nuts.

Bar Hanger Features include:

- Pre-installed, captive
- Housing can be positioned at any point within 24" joist span
- Score lines allow "tooless" shortening for 12" joists
- Bar hangers may be repositioned 90°
- Pass-N-Thru™ bar hangers overlap for toolless shortening to less than 12".
- Unique arrowhead design provides rapid installation.
- Hanger bars fit onto T-bar spline




for quick alignment

Installation Features

- 7 1/2" height allows use in 2x8 construction.
- Housing adjusts for ceilings up to 1 3/8" thick.
- Shipping insert protects socket from paint overspray.

Listings

- UL Listed for Damp Location
- UL listed for Feed Through
- UL listed for Direct Contact with Insulation and combustible material
- CSA Certified
- State of California Title 24
- Washington State Energy Code
- International Energy Conservation Code (IECC)
- New York State Energy Conservation Construction Code (NY-ECCC)
- Model Energy Code (MEC)
- Certified Under ASTM-E283



H5RICAT

AIR-TITE™ IC REMODEL HOUSING



- For insulated ceilings and direct contact with insulation
- Can be installed from below the ceiling
- AIR-TITE housing prevents airflow between attic and living areas
- Upgraded junction box feature - Quick-Connect connectors

For remodeling installations where housing will be in direct contact with insulation. Integral thermal protector provides positive protection against over-lamping.

Housing Features

- Integral thermal protector guards against over-lamping.
- Socket snaps into trim for consistent lamp positioning.
- Junction box is listed for through branch circuit wiring and has seven 1/2" knockouts with true pry-out slots.
- Three quick connect wire connectors eliminate need for

- additional wire nuts.
- Four NM sheathed cable pryouts with integral strain relief simplify NM sheathed cable installation.



- Halo name embossed on top

Installation Features

- 7 1/2" height allows use in 2" x 8" joist construction.
- Integral flange secures fixture against ceiling.
- Four remodel clips secure housing and accommodate 1/2" and 5/8" ceiling thickness.
- Shipping insert protects lamp socket from paint over-spray.

Listings

- UL Listed for Damp Location
- UL listed for Feed Through
- UL listed for Direct Contact with Insulation and combustible material
- CSA Certified
- State of California Title 24
- Washington State Energy Code
- International Energy Conservation Code (IECC)
- New York State Energy Conservation Construction Code (NY-ECCC)
- Model Energy Code (MEC)
- Certified Under ASTM-E283




NOTE: Housing shown with trim and lamp for reference only. Housing and trim must be ordered separately. Lamp not included unless otherwise stated.

HALO®


**H5ICAT
H5RICAT**

H25ICAT

BAFFLES



5010 Baffle
Finish: White Trim Ring with Black Baffle (5010), White Trim Ring with White Baffle (5010W), Silver Trim Ring with Black Baffle (5010SL)
Lamp: H5ICAT: 60W BR30, 50W PAR30
 H5RICAT: 60W BR30, 50W PAR30, 50W PAR30L
Height: 2 1/16" (52mm) **OD:** 6 1/2" (165mm)



New Finish




5014 Metal Baffle
Finish: White Trim Ring with White Baffle (5014P)
Lamp: H25ICAT: 50W PAR30, 65W BR30, 75W PAR30L,
OD: 6 1/2" (165mm)


ADJUSTABLES



5060 Gimbal - 25° Tilt
Finish: White (5060P)
Lamp: H5ICAT, H5RICAT: 50W PAR30
 H25ICAT: 50W R30, 50W PAR30
Aperture: 3 1/4" (82mm) **OD:** 6 1/2" (165mm)




5070 Eyeball - 30° Tilt
Finish: White (5070P), Polished Brass (5070PB), Silver (5070SL)
Lamp: H5ICAT, H5RICAT: 75W PAR30
 H25ICAT: 75W PAR30
OD: 6 1/2" (165mm)



New Finish




5071 Eyeball - 30° Tilt
Finish: White (5071P)
Lamp: H5ICAT, H5RICAT: 50W R20, 50W PAR20
 H25ICAT: 50W R20, 50W PAR20
OD: 6 1/2" (165mm)




LENSES AND DIFFUSERS



5050 Shower Light
Finish: White Trim Ring with Glass Diffuser, Wet Location Listed (5050PS)
Lamp: H5ICAT, H5RICAT: 40W A19, 50W PAR30
 H25ICAT: 40W A19, 50W PAR30
OD: 6 1/2" (165mm)



5051 Frosted Lens Shower Light
Finish: White Trim Ring with Frosted Diffuser, Wet Location Listed (5051PS)
Lamp: H5ICAT, H5RICAT: 35W PAR30L
Height: 3" (76mm) **OD:** 6 1/2" (165mm)



OPEN



5000 Splay Trim
Finish: White (5000P)
Lamp: H5ICAT, H5RICAT: 65W BR30, 75W R30, 75W PAR30
 H5RICAT: 50W PAR30, 60W BR30, 75W PAR30L
Height: 1 7/8" (48mm) **OD:** 6 1/2" (165mm)

