

Two Gang:


Residential Switch or Receptacle Box

Series P-442



Cu. In. Volume	Catalog Number	Component Description	D	W	H	UPC# 85339	Std. Pkg. Qty.	Std. Pkg. Wt. (lb.)
43.5	P-442*	Two gang, angled nails, molded-in Speed Klamps™	3-9/16	4	3-3/4	44000	50	18
43.5	P-442QT	Two gang, angled nails, Quick Thread™ device holes, molded-in Speed Klamps™	3-9/16	4	3-3/4	44001	50	18

Series P-442H



Cu. In. Volume	Catalog Number	Component Description	D	W	H	UPC# 85339	Std. Pkg. Qty.	Std. Pkg. Wt. (lb.)
43.5	P-442H*	Two gang, face bracket side mount hanger, molded-in Speed Klamps™	3-9/16	4	3-3/4	44002	50	21
43.5	P-442HQT	Two gang, face bracket side mount hanger, Quick Thread™ device holes, molded-in Speed Klamps™	3-9/16	4	3-3/4	44003	50	21

P-240OW



Cu. In. Volume	Catalog Number	Component Description	D	W	H	UPC# 85339	Std. Pkg. Qty.	Std. Pkg. Wt. (lb.)
40.0	P-240OW	Two gang, wing brackets, ears, molded-in Speed Klamps™, use LVP-2 partition for dual voltage applications	3-25/64	4-7/64	3-11/16	24912	24	11

Three Gang:


Residential Switch or Receptacle Box

Series P-643




Cu. In. Volume	Catalog Number	Component Description	D	W	H	UPC# 85339	Std. Pkg. Qty.	Std. Pkg. Wt. (lb.)
64.0	P-643*	Three gang, angled nails, molded-in Speed Klamps™	3-9/16	5-13/16	3-3/4	46302	20	10
64.0	P-643QT	Three gang, angled nails, Quick Thread™ device holes, molded-in Speed Klamps™	3-9/16	5-13/16	3-3/4	46301	20	10

Series P-643H



Cu. In. Volume	Catalog Number	Component Description	D	W	H	UPC# 85339	Std. Pkg. Qty.	Std. Pkg. Wt. (lb.)
64.0	P-643H*	Three gang, face bracket side mount hanger, molded-in Speed Klamps™	3-9/16	5-13/16	3-3/4	46303	20	11
64.0	P-643HQT	Three gang, face bracket side mount hanger, Quick Thread™ device holes, molded-in Speed Klamps™	3-9/16	5-13/16	3-3/4	46304	20	11

P-352OW



Cu. In. Volume	Catalog Number	Component Description	D	W	H	UPC# 85339	Std. Pkg. Qty.	Std. Pkg. Wt. (lb.)
52.0	P-352OW	Three gang, wing brackets, ears, molded-in Speed Klamps™, use LVP-2 partition for dual voltage applications	3-25/64	5-59/64	3-11/16	33201	12	8

* Indicates model shown • See page 32 for Attachment Coding descriptions

