

# DURACELL® PROCELL®

## ALKALINE BATTERIES

DURACELL® PROCELL® alkaline batteries deliver outstanding performance and reliability. Major advantages are:

- long lasting and dependable – even after seven years of storage
- last up to ten times longer than super heavy duty zinc carbon batteries in power demanding applications
- long service life at high drain discharges
- operate reliably in temperature extremes of -20°C to 54°C
- date coded to ensure freshness
- economical bulk packaging for professional applications
- contain no added mercury



### PC1300

SPECIFICATIONS	
<b>Size/System:</b>	Size D Alkaline
<b>Voltage:</b>	1.5
<b>Max. Diameter:</b>	1.346"
<b>Max. Height:</b>	2.421"
<b>Average Weight:</b>	4.86 oz (138.0g)
<b>Maximum Volume:</b>	3.44 in. <sup>3</sup> (56.4cm. <sup>3</sup> )
<b>Terminals:</b>	Flat
<b>Operating Temperature Range:</b>	-4°F to 130°F (-20°C to 54°C)
<b>Primary Usage:</b>	Flashlights, Radios, Tape Recorders



### PC1400

SPECIFICATIONS	
<b>Size/System:</b>	Size C Alkaline
<b>Voltage:</b>	1.5
<b>Max. Diameter:</b>	1.031"
<b>Max. Height:</b>	1.969"
<b>Average Weight:</b>	2.29 oz (65.0g)
<b>Maximum Volume:</b>	1.64 in. <sup>3</sup> (26.9cm. <sup>3</sup> )
<b>Terminals:</b>	Flat
<b>Operating Temperature Range:</b>	-4°F to 130°F (-20°C to 54°C)
<b>Primary Usage:</b>	Flashlights, Radios, Tape Recorders



### PC1500

SPECIFICATIONS	
<b>Size/System:</b>	Size AA Alkaline
<b>Voltage:</b>	1.5
<b>Max. Diameter:</b>	.571"
<b>Max. Height:</b>	1.988"
<b>Average Weight:</b>	0.83 oz (23.6g)
<b>Maximum Volume:</b>	0.51 in. <sup>3</sup> (8.4cm. <sup>3</sup> )
<b>Terminals:</b>	Flat
<b>Operating Temperature Range:</b>	-4°F to 130°F (-20°C to 54°C)
<b>Primary Usage:</b>	Pagers, Remotes, Flashlights, Calculators



### PC2400

SPECIFICATIONS	
<b>Size/System:</b>	Size AAA Alkaline
<b>Voltage:</b>	1.5
<b>Max. Diameter:</b>	.413"
<b>Max. Height:</b>	1.752"
<b>Average Weight:</b>	0.39 oz (11.0g)
<b>Maximum Volume:</b>	0.23 in. <sup>3</sup> (3.8cm. <sup>3</sup> )
<b>Terminals:</b>	Flat
<b>Operating Temperature Range:</b>	-4°F to 130°F (-20°C to 54°C)
<b>Primary Usage:</b>	Pagers, Flashlights, TV Remotes



### PC1604

SPECIFICATIONS	
<b>Size/System:</b>	9 Volt Alkaline
<b>Voltage:</b>	9.0
<b>Max. Length:</b>	.689"
<b>Max. Width:</b>	1.043"
<b>Max. Height:</b>	1.909"
<b>Average Weight:</b>	1.62 oz (45.9g)
<b>Maximum Volume:</b>	1.39 in. <sup>3</sup> (22.8cm. <sup>3</sup> )
<b>Terminals:</b>	Miniature Snap
<b>Operating Temperature Range:</b>	-4°F to 130°F (-20°C to 54°C)
<b>Primary Usage:</b>	Infusion Pumps, Wireless Microphones, Smoke Alarms, Radios

## Comprehensive Battery Cross Reference

### DURACELL® PROCELL® ALKALINE BATTERIES

DURACELL/ PROCELL	Voltage	Type	NEDA Industrial/ Consumer	Eveready Industrial/ Consumer	Rayovac Industrial/ Consumer	Bright Star Consumer	Panasonic Industrial
PC1300	1.5	D	13AC/13A	EN95/E95	AL-D/813	7520	AM1
PC1400	1.5	C	14AC/14A	EN93/E93	AL-C/814	7522	AM2
PC1500	1.5	AA	15AC/15A	EN91/E91	AL-AA/815	7524	AM3
PC1604	9.0	9 VOLT	1604AC/1604A	EN22/E22	AL-9V/A1604	7590	6AM6
PC2400	1.5	AAA	24AC/24A	EN92/E92	AL-AAA/824	7526	AM4

### DURACELL® PROCELL® ALKALINE LANTERN BATTERIES

PROCELL	Voltage	Type	NEDA Industrial/Consumer	Eveready Industrial/Consumer	Koehler-Bright Star
PC903	7.5	Screw Terminal Lantern	903AC/—	EN715/—	—
PC915	6.0	Screw Terminal Lantern	915AC/915A	—/—	—

### DURACELL® PROCELL® ELECTRONIC BATTERIES

PROCELL	Voltage	Eveready	Panasonic	Kodak	Varta	Sanyo	Rayovac	Maxell	NEDA	IEC	Other
PL123A	3.0	EL123AP	CR123A	K123LA	CR123A	CR123A	RL123A	CR123	5018LC	CR17345	—
PC7K67	6.0	539	4LR-61	KJ	4018	—	RJ-1	—	1412AP	4LR61	Size J
PC9100	1.5	E90	AM5	KN	4001	—	RN-2	—	910A	LR1	Size N

### DURACELL® PROCELL® MEDICAL APPLICATION BATTERIES

PROCELL	Voltage	Type	Eveready	NEDA	Ultralife
DA146	8.4	Zinc Air	AC146X	7004Z	—
PL1604	9.0	Lithium	L522	1604LC	U9VL

### DURACELL® PROCELL® PROFESSIONAL FLASHLIGHTS

PROCELL	Voltage	Type	Eveready	Rayovac	Koehler-Bright Star	Panasonic
PCECON-W	3.0	Economy, Lightweight Design, Bright Krypton Bulb	3251WH	—	—	—
PCL4D	6.0	Industrial Lantern, Heavy Duty Construction w/Battery Adapter	2081IND	L295-S	2001	—
PCVOYA	3.0	Heavy Duty Rubber Construction, Weather Resistant	R215IND	—	—	—
PCEXPD	3.0	Heavy Duty Rubber Construction, Weather Resistant	4250IND	—	RBR219	RBD210
PCECON-B	3.0	Economy, Lightweight Design, Bright Krypton Bulb	3251R	IN2	2618	2618
PCECON-BM	3.0	Economy, Lightweight Design, 20lb. Magnet, Bright Krypton Bulb	1251	IN2-ML	1618-ML	1618
PCMSHA	3.0	UL and MSHA Approved, Safety High Density Polypropylene, Spare Bulb Holder	1259	IN2-MS	2117	—
PCPEN	3.0	Slim, Aluminum Design Penlight w/Pocket Clip and Prefocused Bulb	6212WH	V2AAA-B	100	—
PCIND	3.0	Heavy Duty Polypropylene, Hanger Ring and Switch Guard, Spare Bulb Holder	E250Y	IN2-K	K-2618	—