

USE WITH LED, CFL OR INCANDESCENT BULBS



Use up to 150W bulbs

Add a Hazardous Handlamp for a Complete System



FEATURES:

- Enclosures are designed to comply with requirements for Class I, Div 1 - Groups C & D and Class II, Groups F & G
- Built to NEC standards
- Indoor or outdoor use
- Rugged fabricated steel and cast aluminum construction
- 30 Amp / 600 Volt advanced slip ring assembly
- Threaded junction box and slip ring enclosure
- SOW-A cable on factory assembled models
- Spring activated ratchet
- 4-roller adjustable cable guide
- Maximum dimensions: 14 1/2" H x 14 1/2" W x 17" D
- Note: 5 additional feet of cable required for safety wrap and hookup

8000 Series Hazardous Duty Reel Selection Guide

SOW Cable Gauge & Conductors	Length of Cable	Reel with Cable Only	Reel w/ Hazardous Duty Handlamp	
			2600	2500
16/3	20'	8163-20	8163-20-XPI	8163-20-XPF
16/3	40'	8163-40	8163-40-XPI	8163-40-XPF
16/3	50'	8163-50	8163-50-XPI	8163-50-XPF
16/4	20'	8164-20		
16/4	40'	8164-40		
16/4	50'	8164-50		
14/3	20'	8143-20	8143-20-XPI	8143-20-XPF
14/3	40'	8143-40	8143-40-XPI	8143-40-XPF
14/3	50'	8143-50	8143-50-XPI	8143-50-XPF
14/4	20'	8144-20		
14/4	40'	8144-40		
14/4	50'	8144-50		

Note: 1. Consult factory for listings/certification status when priced with outlet, plug or light accessories.

