

Product Number: 74377

Order Abbreviation: VAPOR1B/040UNVD850/48EC/GR

General Description: Vapor Tight 1B, 40 watts, 5000K, 120-277V, 0-10V dimmable, etched lens, canopy distribution, gray painted finish



| Product Information | |
|--|------------------------------------|
| Power Factor | ?0.90 |
| Primary Lamp Type | SMD |
| Minimum Operating Temperature - Celsius | -40 |
| Minimum Operating Temp - Fahrenheit | -40 |
| Total Harmonic Distortion (THD) | ?20 % |
| Efficacy (LPW) | 137 |
| Abbrev. With Packaging Info. | VAPOR1B040UNVD85048ECGR 4/CS 1/SKU |
| Color Temperature/CCT (K) | 5000 |
| Ordering Abbreviation | VAPOR1B/040UNVD850/48EC/GR |
| Lumens | 5300 |
| Nominal Voltage (V) | 120.00 |
| Nominal Wattage (W) | 40.00 |
| UPC Code | UPC046135743771 |
| Color Rendering Index (CRI) | >80 |
| Lumens (lm) | 5300 |
| Wattage (W) | 40.00 |
| Accessories | Chain mount bracket |
| Color Range | 5000 K |
| Connectors | Quick Disconnect |
| Energy Star Rated | No |
| Fixture Warranty | 5 years |
| Housing | Polycarbonate (PC) |
| Luminaire Finish | Gray |
| Luminaire Type | Vapor-tight |
| Maximum Operating Temperature-Celsius | 40 |
| Maximum Operating Temperature-Fahrenheit | 104 |
| Power Input | 40 |
| Mounting | Surface, Pendant, Suspended |
| Dimensions | 48.5x4x3.3 |
| Certification Listing | cULus, FCC, RoHS, DLC |