




300 lbs.
TYPE IA
load capacity*
*Includes weight of user plus materials

FIBERGLASS

PLATE CONNECT EXTENSION LADDER


FE7000 SERIES



D-Shaped or Round Rungs
Tempered, serrated aluminum rungs provide for a slip-resistant surface.



Outside Slide Guides
Two extra heavy duty outside slide guides secured to top of base section with four rivets per guide for maximum strength. Over extending stop on fly section.



Mar-Resistant Rail End Caps
Impact resistant caps on all rail ends provide rail protection for longer life and protect work surfaces from marring.




Full Metal Boot™
Extra heavy duty cast aluminum shoes with thick rubber tread. Exclusive Louisville Ladder design. Full swivel safety shoe can be used with tread down or in spike position.

FEATURING THE EXCLUSIVE
FULL METAL BOOT



QuickLatch®
QuickLatch® equipped runglock provides easier method of securing fly and base sections when extended. One-finger operation. Patent #5429207



Aluminum Plate Connection Rungs
Aluminum rungs are hydraulically double crimped to aluminum plate. Each plate is fastened to side rails with four solid aluminum rivets.



D RUNG
SINGLE LADDERS

MODEL	TOTAL LENGTH	APPROX. WEIGHT	APPROX. CUBES
FE7108	8'	18	3.0
FE7110	10'	23	3.9
FE7112	12'	27	4.8
FE7114	14'	31	5.5
FE7116	16'	37	6.4
FE7118	18'	54	9.3
FE7120	20'	60	10.3

ROUND RUNG
SINGLE LADDERS

MODEL	TOTAL LENGTH	APPROX. WEIGHT	APPROX. CUBES
FE7508	8'	17	3.0
FE7510	10'	23	3.9
FE7512	12'	27	4.8
FE7514	14'	30	5.5
FE7516	16'	36	6.4
FE7518	18'	49	13.8
FE7520	20'	54	15.3

D-RUNG
TWO SECTION EXTENSION LADDERS

MODEL	TOTAL LENGTH	LENGTH EACH SECTION	MAX. EXTENDED LENGTH	APPROX. WEIGHT	APPROX. CUBES
FE7216	16'	8'	13'	34	5.7
FE7220	20'	10'	17'	45	7.1
FE7224	24'	12'	21'	53	9.3
FE7228	28'	14'	25'	61	10.8
FE7232	32'	16'	29'	72	12.3
FE7236	36'	18'	32'	108	16.4
FE7240	40'	20'	35'	117	18.2

ROUND RUNG
TWO SECTION EXTENSION LADDERS

MODEL	TOTAL LENGTH	LENGTH EACH SECTION	MAX. EXTENDED LENGTH	APPROX. WEIGHT	APPROX. CUBES
FE7616	16'	8'	13'	34	6.2
FE7620	20'	10'	17'	44	7.7
FE7624	24'	12'	21'	52	9.3
FE7628	28'	14'	25'	60	10.8
FE7632	32'	16'	29'	71	12.3
FE7636	36'	18'	32'	100	16.9
FE7640	40'	20'	35'	110	18.7

300 lbs.
TYPE IA
load capacity*
*Includes weight of user plus materials


FIBERGLASS

EXTENSION LADDER

FE3200 SERIES



QuickLatch®
QuickLatch® equipped runglock provides easier method of securing fly and base sections when extended. One-finger operation. Patent #5429207




Swivel Safety Shoes
Heavy duty plated steel shoes with thick rubber tread. Shoe can be used with tread down or in spike position.



Outside Slide Guides
Two extra heavy duty outside slide guides secured to top of base section with four rivets per guide for maximum strength. Over extending stop on fly section.



D-Shaped Rungs
Flat top, D-shape provides greater standing area than round rungs. Fully serrated for slip-resistant surface.



Mar-Resistant Rail End Caps
Impact resistant caps on all rail ends provide rail protection for longer life and protect work surfaces from marring.



D-RUNG
TWO SECTION EXTENSION LADDERS

MODEL	TOTAL LENGTH	LENGTH EACH SECTION	MAX. EXTENDED LENGTH	APPROX. WEIGHT	APPROX. CUBES
FE3216*	16'	8'	13'	35	6.8
FE3220	20'	10'	17'	43	8.4
FE3224	24'	12'	21'	50	10.0
FE3228	28'	14'	25'	57	11.6
FE3232	32'	16'	29'	68	13.7
FE3236**	36'	18'	32'	77	15.4
FE3240**	40'	20'	35'	86	17.1

SPECIFICATIONS

SIZES	RAIL DEPTH	STACK HEIGHT	INSIDE BASE	WIDTH FLY	OUTSIDE BASE	WIDTH FLY
16'-28'	3 1/8"	5 3/4"	14 1/16"	13 1/16"	17 1/8"	16 1/8"
32'-40'	3 3/8"	6 1/8"	15 3/8"	14 3/8"	17 1/16"	16 1/16"

*Does not include rope and pulley
**Type I, 250 lb. rated

STRAIGHT LADDERS NOT AVAILABLE IN FE3200 SERIES